




AMG BRAND G80 CHAIN CONNECTING LINK



FEATURES

- Forged super alloy steel - quenched and tempered
- Suitable for EN818-2 G80 chains
- Individually proof tested at 2 times WLL
- All load pins are 100% individually inspected and tested
- Complies with AS3776/EN1677
- Fatigue tested at 1.5 x WLL for 20000 cycles
- 100% Magnaflux crack detection
- Yellow powder plastified finish
- Test certificates available




Code	Weight (kg)	WLL (t)	A	B	w	I	K	H
AMG074HL-6	0.08	1.1	15	7.5	58	42	7	
AMG074HL-7/8	0.146	2	18	9.5	79.5	60.5	8.5	
AMG074HL-10	0.3	3.2	25	12	90.5	68	11.5	
AMG074HL-13	0.65	5.3	29	15	117	87	15	
AMG074HL-16	1.15	8	34.5	19.8	148	108.4	19.8	
AMG074HL-18/20	2.1	12.5	41	24	169.5	121.5	24	

TiTAN CHAIN CONNECTOR



FEATURES

- Chain connectors provide fast, easy assembly without the need for special tools
- Designed for attaching hooks, master links and other fittings to Grade 80 alloy steel chains
- Individually proof tested at 2 times WLL
- Individually magnetic particle crack tested
- Complies with AS3776/EN1677
- Yellow powder plastified finish
- Test certificates available




Code	Size	Weight (kg)	WLL (t)	Dimensions (mm)		
				A	B	C
TCL 6	6	0.14	1.1	44	40	16
TCL 7/8	8	0.15	2	54	52	19
TCL 10	10	0.32	3.2	64	65	25
TCL 13	13	0.68	5.3	84	82	30
TCL 16	16	1.26	8	104	103	36
TCL 20	20	2.02	12.5	123	120	44
TCL 22	22	3.18	15	153	139	51
TCL 26	26	4.52	21.2	160	166	57
TCL 32	32	8.2	31.5	175	195	68

TiTAN CLEVIS TRADITIONAL SELF-LOCKING HOOK



FEATURES

- Self-locking hooks are traditionally sized hooks with release mechanism.
- The clevis enables a direct connection to G80 chain
- Once opened the hook will remain open until load is engaged
- Complies with AS3776/EN1677
- Fatigue tested at 1.5 x WLL for 20000 cycles
- 100% Magnaflux crack detection
- Yellow powder plastified finish
- Test certificates available
- Individually proof tested



Code	Weight (kg)	WLL (t)	A	B	H	Dimensions (mm)	
						D	R
T335CSLH-6	0.4	1.1	32	7.5	20	34	96
T335CSLH-7/8	0.7	2	36	9	24	46	118.5
T335CSLH-10	1.5	3.2	46	12	28	58	144
T335CSLH-13	2.7	5.3	59	15	40.5	69	181.5
T335CSLH-16	5.6	8	70	17.5	50.5	86	216
T335CSLH-18/20	10.5	12.5	81	25	62	92	238

