


► Gr8 Weld-On Lifting Point

Designed for use as a fixed anchor and/or lifting point. Welding instructions supplied with each unit.

Test certificates supplied.

Applications: Fixed anchor, lashing or lifting point




WLL (tonnes)	W (mm)	K (mm)	R (mm)	L (mm)	Mass (kg)	Part No.	Markings
1.0	50	38	24	105	0.5	42285	DAA - 1 tonne
3.0	58	48	29	112	0.8	42286	DAA - 3 tonne
5.0	64	61	33	154	1.8	42287	DAA - 5 tonne
8.0	61	73	34	169	2.6	42288	DAA - 8 tonne
10.0	75	73	41	191	3.1	42289	DAA - 10 tonne
15.0	91	93	50	234	6.5	42290	DAA - 15 tonne

► Gr8 Bolt-On Tie Down Point

Designed for use as a fixed anchor or lifting point. Supplied without bolt.

Test certificates supplied.

Applications: Fixed anchor, lashing or lifting point



WLL (tonnes)	A (mm)	B (mm)	R (mm)	M (mm)	K (mm)	L (mm)	Mass (kg)	Part No.	Markings
1.0	50	72	24	14	98	139	0.8	42277	DAB - 1 tonne
3.0	58	84	29	16	114	144	1.1	42278	DAB - 3 tonne
5.0	64	116	33	20	160	203	2.5	42279	DAB - 5 tonne