




**cromox Oblong Master CAGF. Grade 60**  
for 1- and 2-leg chain slings. sand blasted

All master links have a flattened section to allow the use of connectors (e.g. clevis shackles type CGS)

Type	W.L.L.		for Chain		Dimensions mm			Weight kg
	t		1 – leg	2 – leg	d	t	b	
*KW-CAGF10	0.60		5	4	10	80	50	0.150
KW-CAGF13	1.50		6/7/8	5/6	13	110	60	0.340
KW-CAGF16	2.40		10	7/8	16	110	60	0.530
KW-CAGF18	3.35		-	10	18	135	75	0.800
KW-CAGF22	6.00		13/16	13	22	160	90	1.500
KW-CAGF26	8.00		18	16	26	180	100	2.300
KW-CAGF32	12.00		20	18	32	200	110	3.900
*KW-CAGF36	16.00		-	20	36	260	140	6.350


\*On Request. \*Angle of indination 90°



**cromox Sub-Assembly CAKF. Grade 60**  
for 3- and 4-leg chain slings. sand blasted


Type	W.L.L.		for Chain	Dimensions mm			Weight kg
	90°	120°		d	t	b	
*CAKF13/10	1.25	0.90	5	A 13 B 10	110 44	60 25	0.520
KW-CAKF16/13	2.50	1.80	6	A 16 B 13	110 54	60 25	0.970
KW-CAKF18/16	3.15	2.25	7/8	A 18 B 16	135 70	75 34	1.600
KW-CAKF22/16	5.00	3.60	10	A 22 B 18	160 85	90 40	2.760
*CAKF26/22	8.00	5.70	13	A 26 B 22	180 115	100 50	4.450
*CAKF32/26	10.00	7.50	16	A 32 B 26	200 140	110 65	7.550

\*On Request.



**cromox Sub-Assembly CAKF. Grade 50**  
for 3- and 4-leg chain slings. sand blasted

Type	W.L.L.		for Chain	Dimensions mm			Weight kg
	90°	120°		d	t	b	
KW-178622BK	1.70	1.25	8	A 22 B 16	160 70	90 34	2.300
KW-178626BK	2.80	2.00	10	A 26 B 18	180 85	100 40	3.560



**CROMOX®**

