


**cromox Sub-Assembly for Ropes
CAKS. Grade 60 blasted**


Type	W.L.L. t		Dimensions mm			Weight
	45°	60°	d	t	b	ca.kg
CAKS16/13	1.80	1.25	A 16 B 13	110 110	60 60	1.210
CAKS16/16	2.40	1.70	A 16 B 16	110 110	60 60	1.590
CAKS18/16	3.25	2.25	A 18 B 16	135 110	75 60	1.860
CAKS22/18	5.00	3.50	A 22 B 18	160 135	90 75	3.100
CAKS26/22	8.50	5.95	A 26 B 22	180 160	100 90	5.400
CAKS32/26	10.75	7.50	A 32 B 26	200 180	110 100	8.500
CAKS36/32	13.60	9.50	A 36 B 32	260 200	140 110	14.150



**cromox Oblong Master CAG. Grade 60
1- and 2-leg. sand blasted**

Type	W.L.L.	for Chain		Dimensions mm			Weight
	t	1 - leg	2 - leg	d	t	b	kg
*CAG 8	0.30	4	-	8	54	30	0.070
KW-CAG10	0.60	5	4	10	80	50	0.150
KW-CAG13	1.50	6/7/8	5/6	13	110	60	0.340
*CAG 16	2.40	10	7/8	16	110	60	0.530
*CAG 18	3.35	-	10	18	135	75	0.800
*CAG 22	6.00	13/16	13	22	160	90	1.500
*CAG 26	8.00	18	16	26	180	100	2.300
*CAG 32	12.00	20	18	32	200	110	2.900
*CAG 36	16	-	20	36	260	140	6.350


*On Request.



**cromox Sub-Assembly CAK. Grade 60
3- and 4-leg. sand blasted**

Type	W.L.L. t	for Chain	Dimensions mm			Weight	
	90°		120°	d	t	b	kg
CAK 10/ 8	0.75	0.55	4	A10 B 8	80 35	50 19	0.240
CAK 13/10	1.25	0.90	5	A13 B10	110 44	60 25	0.520
CAK 16/13	2.50	1.80	6/7	A16 B13	110 54	60 25	0.970
CAK 18/16	3.15	2.25	8	A18 B16	135 70	75 34	1.600
CAK 22/18	5.00	3.60	10	A22 B18	160 85	90 40	2.760
CAK 26/22	8.00	5.70	13	A26 B22	180 115	100 50	4.450
CAK 32/26	10.00	16	16	A32 B26	200 140	110 65	7.550

This section on Request.



cromox®