


Wire Rope Galv 35x7 Compacted Non Rotating RHLL G2160 (WRG 357)



PN	Description	Size	Indicative MBS	Reel Size	Unit	Weight
		mm	kN	m		Approx Kg/100mts
8165 08 I	W/Rope Galv 35x7 Compacted Non Rotating RHLL 8mm G2160	8	62	500	m	31.81
8165 10 I	W/Rope Galv 35x7 Compacted Non Rotating RHLL 10mm G2160	10	97	500	m	49.3
8165 10 I BM	W/Rope Galv Nylon Blk 35x7 Compacted Non Rotating RHLL 10mm G2160	10	97	500	m	49.3
8165 16 I	W/Rope Galv 35x7 Compacted Non Rotating RHLL 16mm G2160	16	249	500	m	127.23
8165 16 I P	W/Rope Galv 35x7 Compacted Non Rotating PFC RHLL 16mm G2160	16	249	500	m	127.23
8298 10 I	W/Rope Galv 35x7 Non rotating RHLL 10mm G2070 A2 Lube	10	80	500	m	45.4

Please note:

Breaking strains provided for wire rope are indicative only.

They should only be used as a guide as they may vary according to manufacturing specifications.

Please check tensile strength (Grade) and MBS (Minimum Breaking Strain) at time of ordering to confirm.

Additional sizes of wire rope are available on request