


Wire Rope Galv 6x25FW (12/6+6/1) IWRC G1770 (WRG 625)



PN	Description	Size	Indicative MBS	Reel Size	Unit	Weight
		mm	kN	m		Approx Kg/100mts
6216 10	W/Rope Galv 6x25 FW IWRC 10mm G1770	10.0	63		m	40
TBA	W/Rope Galv 6x25 IWRC 11mm G1770	11.0	76.2		m	48.4
6216 14	W/Rope Galv 6x25 FW IWRC 14mm G1770	14.0	123	500	m	82
TBA	W/Rope Galv 6x25 IWRC 16mm G1770	16.0	161		m	102
6216 20	W/Rope Galv 6x25 FW IWRC 20mm G1770	20.0	252	500	m	167

Wire Rope Galv 6x25FW (12/6+6/1) IWRC G2070 (WRG 625)

PN	Description	Size	Indicative MBS	Reel Size	Unit	Weight
		mm	kN	m		Approx Kg/100mts
0486 11	W/Rope Galv 6x25 FW IWRC 11mm G2070	11.0	89.2		m	48.4
0486 14 I	W/Rope Galv 6x25 FW IWRC 14mm G2070	14.0	144.7	1000	m	82
0486 16	W/Rope Galv 6x25 FW IWRC 16mm G2070	16.0	188.7		m	102

Please note:

Breaking strains provided for wire rope are indicative only.

They should only be used as a guide as they may vary according to manufacturing specifications.

Please check tensile strength (Grade) and MBS (Minimum Breaking Strain) at time of ordering to confirm.

Additional sizes of wire rope are available on request