




## Wire Rope Galv 6x36WS IWRC G1960 (WRG 636)



PN	Description	Size	Indicative MBS	Reel Size	Unit	Weight
		mm	kN	m		Approx Kg/100mts
2195 07 G1960	W/Rope Galv 6x36 IWRC 7mm G1960	7.0	34.2		m	20
2195 08 G1960	W/Rope Galv 6x36 IWRC 8mm G1960	8.0	44.7		m	26.2
2195 09 I G1960	W/Rope Galv 6x36 IWRC 9mm G1960	9.0	56.5	500	m	33.1
8205 10	W/Rope Galv 6x36WS IWRC 10mm G1960	10.0	69.8		m	40.9
2195 11 I G1960	W/Rope Galv 6x36 IWRC 11mm G1960	11.0	84.4	500	m	49.5
2195 12 I G1960	W/Rope Galv 6x36 IWRC 12mm G1960	12.0	100	1000	m	58.9
8205 13	W/Rope Galv 6x36WS IWRC 13mm G1960	13.0	118		m	69.1
8205 14	W/Rope Galv 6x36WS IWRC 14mm G1960	14.0	137		m	80.2
8205 15	W/Rope Galv 6x36WS IWRC 15mm G1960	15.0	157		m	92
2195 16 G1960	W/Rope Galv 6x36 IWRC 16mm G1960	16.0	179	500	m	105
8205 18	W/Rope Galv 6x36WS IWRC 18mm G1960	18.0	226		m	133
8205 19	W/Rope Galv 6x36WS IWRC 19mm G1960	19.0	252		m	148
8205 20	W/Rope Galv 6x36WS IWRC 20mm G1960	20.0	279		m	164
8205 22	W/Rope Galv 6x36WS IWRC 22mm G1960	22.0	338		m	198
8205 24	W/Rope Galv 6x36WS IWRC 24mm G1960	24.0	402		m	236

**Please note:**

Breaking strains provided for wire rope are indicative only.


They should only be used as a guide as they may vary according to manufacturing specifications.

Please check tensile strength (Grade) and MBS (Minimum Breaking Strain) at time of ordering to confirm.

**Additional sizes of wire rope are available on request**



## Wire Rope Galv 6x36WS IWRC G1960 (WRG 636)



PN	Description	Size	Indicative MBS	Reel Size	Unit	Weight
		mm	kN	m		Approx Kg/100mts
8205 26	W/Rope Galv 6x36WS IWRC 26mm G1960	26.0	472		m	276
8205 28	W/Rope Galv 6x36WS IWRC 28mm G1960	28.0	547		m	321
8205 30	W/Rope Galv 6x36WS IWRC 30mm G1960	30.0	628		m	368
8205 32	W/Rope Galv 6x36WS IWRC 32mm G1960	32.0	715		m	419
8205 35	W/Rope Galv 6x36WS IWRC 35mm G1960	35.0	855		m	501
8205 36	W/Rope Galv 6x36WS IWRC 36mm G1960	36.0	904		m	530
8205 38	W/Rope Galv 6x36WS IWRC 38mm G1960	38.0	1010		m	591
8205 40	W/Rope Galv 6x36WS IWRC 40mm G1960	40.0	1120		m	654
8205 44	W/Rope Galv 6x36WS IWRC 44mm G1960	44.0	1350		m	792
8205 45	W/Rope Galv 6x36WS IWRC 45mm G1960	45.0	1410		m	828
8205 48	W/Rope Galv 6x36WS IWRC 48mm G1960	48.0	1610		m	942
8205 51	W/Rope Galv 6x36WS IWRC 51mm G1960	51.0	1810		m	1060
8205 52	W/Rope Galv 6x36WS IWRC 52mm G1960	52.0	1890		m	1110

**Please note:**

Breaking strains provided for wire rope are indicative only.

They should only be used as a guide as they may vary according to manufacturing specifications.

Please check tensile strength (Grade) and MBS (Minimum Breaking Strain) at time of ordering to confirm.

**Additional sizes of wire rope are available on request**