




Wire Rope Galvanised Steel Core

Wire Rope Galv 7x19 WSC G2070 (WRG 719)



PN	Description	Size	Indicative MBS	Reel Size	Unit	Weight
		mm	kN	m		Approx Kg/100mts
0476	W/Rope Galv 7x19 WSC 3mm G2070	3.0	6.2	1000	m	3.68
2226	W/Rope Galv 7x19 WSC 3.2mm G2070	3.2	7	1000	m	4.2
2229	W/Rope Galv 7x19 WSC 3.5mm G2070	3.5	8.4	1000	m	4.6
0478	W/Rope Galv 7x19 WSC 4mm G2070	4.0	11	1000	m	6.1
0478 IC 250	W/Rope Galv 7x19 WSC 4mm G2070 250m	4.0	11	250	each	6.7
0478 IC 500	W/Rope Galv 7x19 WSC 4mm G2070 500m	4.0	11	500	each	6.7
6764 I	W/Rope Galv 7x19 WSC 4.8mm G2070	4.8	15.8	1000	m	9.5
0479	W/Rope Galv 7x19 WSC 5mm G2070	5.0	17.1	1000	m	9.5
0479 IC 500	W/Rope Galv 7x19 WSC 5mm G2070 500m	5.0	17.1	500	each	9.5
3774 I	W/Rope Galv 7x19 (18x7+WSC) Non Rotating RHOL 5mm G2070	5.0	17	500	m	10.48
0480	W/Rope Galv 7x19 WSC 6mm G2070	6.0	24.7	1000	m	13.7
0480 IC 050	W/Rope Galv 7x19 WSC 6mm G2070 50m	6.0	24.7	50	each	13.7
0480 IC 500	W/Rope Galv 7x19 WSC 6mm G2070 500m	6.0	24.7	500	each	13.7
0481	W/Rope Galv 7x19 WSC 6.3mm G2070	6.3	27.3	1000	m	15.1
0482	W/Rope Galv 7x19 WSC 8mm G2070	8.0	43.9	1000	m	24.4
0482 IC 500	W/Rope Galv 7x19 WSC 8mm G2070	8.0	47.96	500	each	24.4
0484	W/Rope Galv 7x19 WSC 9.5mm G2070	9.5	62	1000	m	34.38
0485	W/Rope Galv 7x19 WSC 10mm G2070	10.0	68.7	1000	m	38.1
0485 I 250	W/Rope Galv 7x19 WSC 10mm G2070 250m	10.0	68.7	250	each	38.1
0485 I 500	W/Rope Galv 7x19 WSC 10mm G2070 500m	10.0	68.7	500	each	38.1
6491 I	W/Rope Galv 7x19 WSC 11mm G2070	11.0	83.2	1000	m	50.6
6032	W/Rope Galv 7x19 WSC 12mm G2070	12.0	98.6	1000	m	54.8
PI 6492 I	W/Rope Galv 7x19 WSC 13mm G2070	13.0	116.1	1000	m	64.3

Breaking strains provided for wire rope are indicative only. They should only be used as a guide as they may vary according to manufacturing specifications. Please check tensile strength (Grade) and MBS (Minimum Breaking Strain) at time of ordering to confirm.

Additional sizes of wire rope are available on request

