


Wire Rope Stainless Steel Grade 316

Wire Rope Stainless Steel 1x19 G316 (WRS 119)



PN	Description	Size	Indicative MBS	Reel Size	Unit	Weight
		mm	kN	m		Approx Kg/100mts
0399 IC	W/Rope SS 1x19 G316 1mm	1.0	0.81	305	m	0.5
0401 IC	W/Rope SS 1x19 G316 1.2mm (3/64)	1.2	1.18	305	m	0.71
0405	W/Rope SS 1x19 G316 1.6mm (1/16)	1.6	2.06	305	m	1.28
0409	W/Rope SS 1x19 G316 2mm (5/64)	2.0	3.08	305	m	2.0
0412	W/Rope SS 1x19 G316 2.4mm (3/32)	2.4	4.42	305	m	2.88
0415	W/Rope SS 1x19 G316 3.2mm (1/8)	3.2	7.86	305	m	5.12
0415 I 50	W/Rope SS 1x19 G316 3.2mm (1/8)	3.2	7.86	305	m	5.12
0415 I 100	W/Rope SS 1x19 G316 3.2mm (1/8) 100m	3.2	7.86	100	each	5.12
0415 I 305	W/Rope SS 1x19 G316 3.2mm (1/8) 305m	3.2	7.86	305	each	5.12
0415 I 1000	W/Rope SS 1x19 G316 3.2mm (1/8) 1000m	3.2	7.86	1000	each	5.12
0418 I	W/Rope SS 1x19 G316 4mm (5/32)	4.0	11.97	305	m	8
0422	W/Rope SS 1x19 G316 4.8mm (3/16)	4.8	17.5	305	m	11.52
6778	W/Rope SS 1x19 G316 5mm	5.0	18.04	305	m	12.5
0426 I	W/Rope SS 1x19 G316 6.4mm (1/4)	6.4	29.73	305	m	20.48
0430	W/Rope SS 1x19 G316 8mm (5/16)	8.0	45.51	305	m	32
0434 I	W/Rope SS 1x19 G316 9.5mm (3/8)	9.5	63.13	305	m	45.12
6007	W/Rope SS 1x19 G316 10mm	10.0	69.95	305	m	50
0440 I	W/Rope SS 1x19 G316 12mm (1/2)	12.0	93.55	305	m	72

Please note:

Breaking strains provided for wire rope are indicative only.

They should only be used as a guide as they may vary according to manufacturing specifications.

Please check tensile strength (Grade) and MBS (Minimum Breaking Strain) at time of ordering to confirm.

Additional sizes of wire rope are available on request