




Wire Rope Stainless Steel 7x19 G304 (WRS 719)



PN	Description	Size	Indicative MBS	Reel Size	Unit	Weight
		mm	kN	m		Approx Kg/100mts
2271 I	W/Rope SS 7x19 G304 2mm (5/64)	2.0	2.74	305	m	1.6
2270 I	W/Rope SS 7x19 G304 2.4mm (3/32)	2.4	3.92	305	m	2.3
2703	W/Rope SS 7x19 G304 3.2mm (1/8)	3.2	6.97	305	m	4.1
0420	W/Rope SS 7x19 G304 4mm (5/32)	4.0	10.68	305	m	6.71
0423	W/Rope SS 7x19 G304 4.8mm (3/16)	4.8	15.36	305	m	9.22
2637 I	W/Rope SS 7x19 G304 5.5mm (7/32)	5.5	20.16	305	m	12.1
0386 I	W/Rope SS 7x19 G304 6mm Metric	6.0	24.11	305	m	14.4
0427	W/Rope SS 7x19 G304 6.4mm (1/4)	6.4	27.44	305	m	16.38
0431	W/Rope SS 7x19 G304 8mm (5/16)	8.0	40	305	m	24.64
0436 I	W/Rope SS 7x19 G304 9.5mm (3/8)	9.5	58.21	305	m	36.1
0442 I	W/Rope SS 7x19 G304 12.7mm (1/2)	12.7	104.08	305	m	64.52
2390 I	W/Rope SS 7x19 G304 20mm (3/4)	20.0	214.62	305	m	160

Please note:

Breaking strains provided for wire rope are indicative only.

They should only be used as a guide as they may vary according to manufacturing specifications.

Please check tensile strength (Grade) and MBS (Minimum Breaking Strain) at time of ordering to confirm.

Additional sizes of wire rope are available on request

