




Wire Rope Stainless PVC Coated 7x19 G316 (WRSP 719)



PN	Description	Size	Indicative MBS	Reel Size	Unit	Weight
		mm	kN	m		
6660 I BLK	W/Rope SS PVC Blk 7x19 G316 3.2-5mm	3.2-5.0	5.99	305	m	5.49
6660 I CLR	W/Rope SS PVC Clear 7x19 G316 3.2-5mm	3.2-5.0	5.99	305	m	5.49
6660 I CLR 1000	W/Rope SS PVC Clear 7x19 G316 3.2-5mm 1000m	3.2-5.0	5.99	1000	each	5.49
2317 I BLK	W/Rope SS PVC Blk 7x19 G316 4-6mm Metric	4.0-6.0	9.19	305	m	8.28
2317 I CLR	W/Rope SS PVC Clear 7x19 G316 4-6mm (5/32)	4.0-6.0	9.19	305	m	8.28
2317 IC CLR M 1000	W/Rope SS PVC Clear 7x19 G316 4-6mm Metric 1000m	4.0-6.0	9.19	1000	each	8.28
0457 I	W/Rope SS PVC Clear 7x19 G316 4.8-6mm (3/16)	4.8-6.0	13.21	305	m	11.93
6616 I	W/Rope SS PVC Clear 7x19 G316 6-8mm (15/64)	6.0-8.0	20.73	305	m	17.03
6616 IC M 1000	W/Rope SS PVC Clear 7x19 G316 6-8mm Metric 100m	6.0-8.0	20.73	1000	each	17.03
0458 I	W/Rope SS PVC Clear 7x19 G316 6.35-7.94mm	6.35-7.94	23.6	305	m	18.26
0458 I 1000	W/Rope SS PVC Clear 7x19 G316 6.35-7.94mm 1000m	6.35-7.94	23.6	1000	each	18.26
6661 I	W/Rope SS PVC Clear 7x19 G316 8-10mm	8.0-10.0	34.39	305	m	28.98
8246 I	W/Rope SS PVC Clear 7x19 G316 3/8-12mm	3/8-12.0				36.86

Please note:

Breaking strains provided for wire rope are indicative only.

They should only be used as a guide as they may vary according to manufacturing specifications.

Please check tensile strength (Grade) and MBS (Minimum Breaking Strain) at time of ordering to confirm.

Additional sizes of wire rope are available on request

