

Chain Size (mm)	WLL (tonnes)	A (mm)	K (mm)	P (mm)	T (mm)	H (mm)	N.W (Kg)	Part No.	Marking	Repair kit Part No.	Repair kit Load pin Part No.
7-8	2.5	9	119	34	20	24	0.9	42428	7+8 1/4	42403	42534
10	4.0	11	142	44	26	30	1.4	42429	10 3/8	42404	42535
13	6.7	14	178	51	30	39	3.0	42430	13 1/2	42405	42536
16	10.0	18	213	60	36	49	5.6	42431	16-10 5/8	42406	42537
20	16.0	21	244	70	53	65	10.8	42432	20-10 3/4	42407	42538
22	19.0	24	273	80	49	63	13.1	42433	22-10 7/8	42408	42539

### » Gr10 Swivel Self Locking Hook

Designed with ball bearing allowing the hook to swivel under load.

Test certificates supplied.

- **Applications:** Chain and wire rope slings
- **Australian Standard:** AS 3776



Chain Size (mm)	WLL (tonnes)	K (mm)	P (mm)	B (mm)	A (mm)	D (mm)	T (mm)	H (mm)	N.W (Kg)	Part No.	Marking	Repair kit Part No.
7-8	2.5	186	34	29	36	13	20	24	1.2	42435	7+8-10 1/4	42403
10	4.0	218	44	34	41	16	26	30	2.0	42437	10-10 3/8	42404
13	6.7	276	51	43	46	21	30	39	4.1	42438	13-10 1/2	42405
16	10.0	329	60	50	61	23	36	49	6.8	42439	16-10 5/8	42406
20	16.0	387	70	82	74	25	53	65	12.6	42440	20-10 3/4	42407
22	19.0	457	80	95	97	33	49	63	19.4	42441	22-10 7/8	42408
26	26.5	535	99	115	123	42	56	69	32.9	42442	26-10 1	42409