

Chain Size (mm)	WLL (tonnes)	B (mm)	D (mm)	E* (mm)	Mass (kg)	Hole Dia** (mm)	Part No.	Markings	Repair kit Part No.
6.0/7.1	1.6	46	43	13	0.1	14	40437	9/32 CM 7	40446
10.0	3.2	62	55	18	0.3	19	40438	10 HAMMERLOK	40447
13.0	5.4	86	80	28	0.8	23	40439	13 HAMMERLOK	40448
16.0	8.0	103	94	32	1.1	27	40440	16 HAMMERLOK	40449
20.0	12.5	121	109	38	1.7	32	40441	18/20 HAMMERLOK	40450
22.0	15.5	131	135	44	2.7	34	40442	20/22 HAMMERLOK	40451
26.0	21.6	146	157	51	4.4	40	40443	26 HAMMERLOK	40452
32.0	32.8	174	197	57	8.1	51	40444	32 HAMMERLOK	40453



* Largest stock diameter of fitting that the Hammerlok™ will accept.

** Minimum hole diameter to accept male leg.

» Gr8 Clevis Self-Lock Hook

Easily and safely closed with one hand, the Gr8 Clevis Self-Lock Hook will lock itself when the load is engaged and will not disengage even if the load is temporarily set down.

Can be mechanically connected to Grade 80 Chain for easy assembly and use.

Test certificates supplied.

- **Applications:** Chain slings
- **Australian Standard:** AS 3776



REPAIR KIT
LOAD PIN

REPAIR KIT
TRIGGER



Chain Size (mm)	WLL (tonnes)	A (mm)	K (mm)	P (mm)	T (mm)	H (mm)	Mass (kg)	Part No.	Markings	Repair kit Trigger Part No.	Repair kit Load Pin Part No.
6	1.1	6	100	29	15	19	0.5	40359Y	YD 6 - 8	42040Y	41122Y
7.1/8.0	2.0	9	119	34	20	24	0.8	40371Y	YD 7 + 8 - 8	40341Y	41123Y
10	3.2	11	143	44	26	30	1.4	40372Y	YD 10 - 8	40342Y	41124Y
13	5.3	14	179	52	30	39	2.9	40373Y	YD 13 - 8	40343Y	41125Y
16	8.0	18	212	60	36	49	5.6	40374Y	YD 16 - 8	41433Y	41126Y
20	12.5	21	243	90	48	62	8.8	40360Y	YD 18/20 - 8	40630Y	41127Y
22	15.0	24	273	80	49	63	14.1	40364Y	YD 22 - 8	40631Y	41128Y

» Gr8 Eye Self-Lock Hook

Easily and safely closed with one hand, the Gr8 Eye Self-Lock Hook will lock itself when the load is engaged and will not disengage even if the load is temporarily set down.

Test certificates supplied.

- **Applications:** Chain and wire rope slings
- **Australian Standard:** AS 3776

