

» Gr8 Clevis Sling Hook

Test certificates supplied.

Hooks without a latch are generally used for specific applications, therefore where there is a risk of the hooks becoming detached during use, a risk assessment shall be conducted in accordance with Section 11 of AS 3776.

- **Applications:** Chain slings
- **Australian Standard:** AS 3776

Chain Size (mm)	WLL (tonnes)	A (mm)	K (mm)	P1 (mm)	T (mm)	H (mm)	Mass (kg)	Part No.	Markings	Repair kit Part No.
6.0	1.1	6	79	23	15	18	0.3	42256Y	YM 6 - 8	41122Y
7.1/8.0	2.0	9	98	27	18	22	0.6	40384Y	YM 7 + 8 - 8	41123Y
10.0	3.2	11	121	34	23	29	1.2	40385Y	YM 10 - 8	41124Y
13.0	5.3	14	147	44	30	37	2.3	40386Y	YM 13 - 8	41125Y
16.0	8.0	18	166	48	39	42	3.8	40387Y	YM 16 - 8	41126Y
20.0	12.5	21	200	56	47	50	6.7	40388Y	YM 20 - 8	41127Y



» HA8 Pinlok Sling Hook

Test certificates supplied.

Hooks without a latch are generally used for specific applications, therefore where there is a risk of the hooks becoming detached during use, a risk assessment shall be conducted in accordance with Section 11 of AS 3776.

- **Applications:** Chain slings
- **Australian Standard:** AS 3776

