

» EHL Series Chain Air Hoist

EHL Air hoists from Endo Kogyo are fitted with rotary vane motors in strong lightweight aluminium bodies, for easy handling in a variety of industrial and construction applications. Variable speed models available in either cord or pendant controls with optional lift heights.

Standard features include:

- Compact and lightweight ensures ease of handling.
- Operation speed depends on the amount of pressure applied to the push buttons or how hard the control rope is pulled.
- Installation - simply connect the air hose.
- Precise variable lifting and high speed.
- Quality load chain allowing high frequency of use.
- Upper and lower limit switches.
- **Applications:** Mining, construction, engineering, offshore
- **Australian Standard:** AS1418.2



Capacity	Part No. 3 Metre (Pendant)	Part No. 3 Metre (Pull Cord)	Model	Lift Speed (m / min)	Load Chain dia (mm) x falls	Headroom (mm)	Weight (kg)	Load Chain Dia x Pitch (mm)	Load Chain Part No.
125kg	44519	NA	AT125K	14.5	4.0 x 1	790	12.5	4 x 12	48351
500kg	49251	49250	EHL05ST	10.5	6.3 X 1	365	19	6.3 X 19	43206
1 Tonne	49253	49252	EHL1TW	5.2	6.3 x 2	440	25	6.3 X 19	43206
1 Tonne	63538	48237	EHL1ST	6.0	7.1 x 1	480	34	7.1 x 21	46745
2 Tonne	48238	48239	EHL2TW	3.0	7.1 x 2	540	42	7.1 x 21	46745
3 Tonne	44181	44998	EHL3TS	3.0	12.5 x 1	585	75	12.5 x 38	46752
6 Tonne	47609	45000	EHL6TW	1.5	12.5 x 2	770	96	12.5 x 38	46752