




TITAN TTC TROLLEY BEAM CLAMP

STANDARD FEATURES

- Easy installation makes it suitable for fixing to hoist, pulleys, etc.
- Adjust quickly to the beam width by turning the main spindle.
- Safety is ensured by the special locking lever.
- The spindle and snap-pin stops are galvanized to protect against corrosion.
- Complies with AS/NZS1418 standard. Proof tested 1.5 x W.L.L.



Model	Load Capacity (t)	I-beam Width Range (mm)	C (mm)	D (mm)	H (mm)	O (mm)	F (mm)	N. W. (kg)
TTC010	1	64-203	46	242	297	22	≈3	14.7
TTC020	2	76-203	55	281	318	22	≈3	29.4
TTC030	3	76-203	62	328	351	24	≈3	44.1
TTC050	5	100-305	71	377	455	28	≈4.5	61.3
TTC100	10	150-305	71	455	500	42	≈4.5	122.6




Also available in black for entertainment industry.

TITAN TBC BEAM CLAMP

STANDARD FEATURES

- Special clamp jaw design applies loads away from flange edge.
- Fits wide range of beams and flange widths.
- Easy and simple mounting.
- Low headroom design.
- Complies with AS4991.2004 standard. Proof tested 2 x W.L.L.



Model	Load Capacity (t)	I-beam Width Range (mm)	B (mm)			F (mm)			N. W. (kg)		
			A (mm)	Min	Max	C (mm)	E (mm)	Min		Max	G (mm)
TBC010	1	75-220	260	180	360	64	215	102	155	25	14.7
TBC020	2	75-220	260	180	360	74	215	102	155	25	29.4
TBC030	3	80-320	354	235	490	103	260	140	225	45	44.1
TBC050	5	80-320	354	235	490	110	260	140	225	45	61.3
TBC100	10	90-320	365	320	505	120	260	170	225	50	122.6



TITAN TPML MAGNET LIFTER

STANDARD FEATURES

- Widely used in machining, fabrication and tooling industries.
- High-performance permanent magnetic materials, patented circuit design.
- Maximum breakaway force is 3.5 times rated lifting power (excluding 5t).
- Handle switches with safety twist for single-handed operation & more safety.
- V" style design at the bottom of lifter, can lift round steel or steel plate.
- Complies with AS4991.2004 standard. Proof tested 2 x W.L.L.



Model	Rated Lifting Capacity (kg)		L (mm)	B (mm)	H (mm)	R (mm)	Test Max. Pull-off Force (kg)	N. W. (kg)
	Steel Plate	Round Steel						
TPML100	100	50	92	64	72	148	350	3
TPML300	300	150	168	99	108	223	1050	12
TPML600	600	300	228	118	123	257	2100	24
TPML1000	1000	500	266	150	158	303	3500	43
TPML1500	1500	750	354	168	172	464	5000	69
TPML2000	2000	1000	394	196	204	470	7000	105
TPML3000	3000	/	431	234	232	576	10500	160
TPML5000	5000	/	522	294	289	728	15000	302

